


LM 200 RFID UHF Antenna

Product Features


- LM200 CP is suitable for UHF RFID applications, such as entrance guard, warehouse management, logistics and retail item management.

Specifications

Frequency Range:	865MFiz~867MFiz
Maximum VSWR:	<1.3:1 Gain: > 9 dBi
H side HPBW:	70° E side HPBW: 70°
Polarization:	Circular Polarization Relative
humidity:	5%~95%
Input Impedance:	50 Ω
Antenna Connection:	N-50KFD (Type N Female)
Size:	258mm x 258mm x 36mm
Weight:	0.91kg(without bracket)
Material:	Engineering Plastic ASA.,
Aluminums Color:	Ivory-white
Enclosure Rating:	IP67
Operational Temperature:	-40°C~+ 85°C
Storage Temperature:	-40°C ~+ 85°C



The photograph of the antenna



The installed dimension of the antenna



The radiation pattern (E side)



No. 7, Sannadhi street, Adambakkam,
Near by St.Thomas Mount Railway station,
Chennai - 600 088, Tamilnadu, India.
Ph.: 044 4352 0740



Office: 044 4352 0740
Mobile: +91 9840336319 | +91 9600010502



E-mail: info@greenfuturz.com, rfid@greenfuturz.com
Website: www.greenfuturz.com